




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : F16L 47/02, 13/007	A1	(11) International Publication Number: WO 99/30073 (43) International Publication Date: 17 June 1999 (17.06.99)
<p>(21) International Application Number: PCT/GB98/03698</p> <p>(22) International Filing Date: 10 December 1998 (10.12.98)</p> <p>(30) Priority Data: 9726154.9 10 December 1997 (10.12.97) GB</p> <p>(71) Applicant (for all designated States except US): PETROTECH- NIK LIMITED [GB/GB]; Maitland Road, Lion Barn Busi- ness Park, Needham Market, Ipswich, Suffolk IP6 8NZ (GB).</p> <p>(72) Inventors; and (75) Inventors/Applicants (for US only): WRIGHT, Wayne, Clifton, Augustus [GB/GB]; Shekinah, 29 Cornwallis Avenue, Linton, Maidstone, Kent ME17 4BW (GB). BOUDRY, John, Alexandre [GB/GB]; Poplar Farm, Buxhall Road, Brettenham, Suffolk IP7 7PA (GB).</p> <p>(74) Agent: COATES, Ian, Harold; Sommerville & Rushton, 45 Grosvenor Road, St. Albans, Hertfordshire AL1 3AW (GB).</p>	<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report.</p>	

(54) Title: CONNECTION BETWEEN A WALL AND-A-PIPE



Secondary Containment Chamber
Connection of 160/110 and 160/90 Pipe

(57) Abstract

A fitting for providing a substantially fluid-tight seal between an opening in a chamber wall (10) and a pipe (4) passing through said opening, said fitting comprising: (i) a tabular sleeve (22) adapted to pass through the opening in the chamber wall (10) and further adapted to allow the pipe (4) to pass through the sleeve (22); (ii) a flange (24), extending radially outwardly from the sleeve (22), a first surface (26) of the flange (24) being configured to contact the chamber wall (10) around substantially the whole circumference of the opening; characterised in that the flange (24) incorporates an energy transfer means at or near the first surface (26), said energy transfer means enabling the first surface (26) and/or the wall of chamber (6) in the vicinity of the flange (24) to be heated to cause the flange (24) and the wall (10) to fuse or bond together in order to form a substantially fluid tight seal.

ABSTRACT

A fitting for providing a substantially fluid-tight seal between an opening in a chamber wall and a pipe passing through the opening, the fitting including a tubular sleeve adapted to pass through the opening in the chamber wall and further adapted to allow the pipe to pass through the sleeve, a flange extending radially outwardly from the sleeve, a first surface of the flange being configured to contact the chamber wall around substantially the whole circumference of the opening wherein the flange incorporates an energy transfer device enabling the first surface and/or wall of chamber in the vicinity of the flange to be heated to cause the flange and the wall to fuse or bond together in order to form a substantially fluid tight seal.